



**POLYCOAT
PRODUCTS**
A Division of American Polymers Corp.

THEMECOAT™ 101
In-Mold Coating
Technical Data Sheet

DESCRIPTION

Themecoat™ 101 is an in-mold coating to enhance the release properties of the Themecoat™ resin systems, with extremely fast drying time for increased efficiency. It is a base color coat that can be stained with pigments to provide various color shades.

FEATURES

- ❖Fast Dry
- ❖Single Component
- ❖Outstanding Flexibility and Impact Resistance
- ❖Good Color Retention
- ❖Provides Stainable Surface

RECOMMENDED USES

- ❖To be used in Conjunction with Dry Color Pigments

COLORS

White

PACKAGING

- 1 gallon cans
- 5 gallon pails

COVERAGE

Themecoat™ 101 theoretical coverage for 1 mil thickness is one gallon per 130-260 sq. ft. Recommended thickness is 1-2 mils.

THINNING

Use Toluol as necessary to provide proper flow and sprayability. Dilution should not be greater than a 1:1 ratio.

APPLICATION PARAMETERS

Minimum surface and ambient temperature is 65°F (18°C).

Dry time to Laminate at 50% RH:

<u>Temperature</u>	<u>Dry Time</u>
75°F (24°C)	5 minutes
100°F (38°C)	3½ minutes
120°F (49°C)	2 minutes

EQUIPMENT CLEANUP

Equipment should be cleaned with an environmentally safe, urethane-grade solvent (alcohol free) as permitted under local regulations immediately after use.

STORAGE

Themecoat™ 101 has a shelf life of one (1) year from date of manufacture in factory sealed containers.

Store containers on wooden pallets to avoid direct contact with the ground.

TECHNICAL DATA

Total Solids by Volume	16 ± 1%
Flash Point, PMCC	24°F
	-4°C
Viscosity, LV 4/60 RPM	200 cps
Weight, ASTM D-1475	8.8 ± 0.3
Volatile Organic Compounds	5.8 lbs/gal
	687 gm/liter
Flexibility	Passes
Accelerate Weathering	No Cracking, Chalks
(G-23 QUV)	or Loss of Property
	after 2000 hours
High Temperature Resistance, ASTM D-5373	
Continuous	180°F (82°C)
Intermittent	200°F (93°C)

LIMITATIONS

Do not open until ready to use.

WARNING

This product contains solvents.

Please read all information in the general guidelines, product data sheets, guide specifications and material safety data sheets (MSDS) before applying material. Published technical data and instructions are subject to change without notice. Contact your local Polycoat Products representative or visit our website for current technical data and instructions.

LIMITED WARRANTY

Polycoat Products warrants its products to be free of manufacturing defects and that they will meet Polycoat Products current published physical properties. Polycoat Products warrants that its products, when properly installed by a state licensed waterproofing contractor according to Polycoat Products guide specifications and product data sheets over a sound, properly prepared substrate, will not allow water migration for a period of one (1) year. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. There are no other warranties by Polycoat Products of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Polycoat Products shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. Polycoat Products shall not be responsible for use of this product in a manner to infringe on any patent held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and/or physical movement of the substrate or structural defects are also excluded from the limited warranty. Polycoat Products reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator.

DISCLAIMER

All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the users responsibility to satisfy himself, by his own information and test, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his use of the product. We do not suggest or guarantee that any hazard listed herein are the only ones which may exist. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements, whether in writing or oral, other than those contained herein shall not be binding upon the manufacturer, unless in writing and signed by a corporate officer of the manufacturer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and Polycoat Products makes no claim that these tests or any other tests, accurately represent all environments.