



**Product Description**

Straight Jacket Tape is a fiberglass mesh tape.

**Color**

Off-White

**FEATURES**

- » Excellent Reinforcement of Stress Areas

**TYPICAL USES**

Straight Jacket Tape is used in the Fire Rated Polydeck® decking systems.

Provides excellent reinforcement for:

- » Joints
- » Cracks
- » Concrete
- » Other High Stress Areas
- » Seams
- » Flashings
- » Plywood

**PACKAGING**

**Single Rolls - 4" x 150' (10.16 cm x 45.7 m)**  
**Sold Individually or in Cases of 18 Rolls**

**TECHNICAL DATA**

<b>Coverage per roll, length, observed</b>	150 ft (3.81 m) 45.7 meters
--	--------------------------------

<b>Thickness, observed</b>	0.007" 0.18 mm
----------------------------	-------------------

<b>Average weight, observed</b>	1.9 oz/sqy 64.4 gm/sqm
---------------------------------	---------------------------

<b>Tensile Strength, ASTM D-1668 II,</b>	
<b>Warp</b>	85 psi (0.6 Mpa)
<b>Fill</b>	85 psi (0.6 Mpa)

<b>Thread, ASTM D-1668 II</b>	
<b>Warp</b>	20
<b>Fill</b>	20

<b>Yarn, ASTM D-1668 II</b>	
<b>Warp</b>	150-1/0
<b>Fill</b>	150-1/0



**Disclaimer:** All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the users responsibility to satisfy himself, by his own information and test, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his use of the product. We do not suggest or guarantee that any hazard listed herein are the only ones which may exist. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements, whether in writing or oral, other than those contained herein shall not be binding upon the manufacturer, unless in writing and signed by a corporate officer of the manufacturer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and Polycoat Products makes no claim that these tests or any other tests, accurately represent all environments. © 2018 Polycoat Products. All rights reserved.

