

Product Description

Polytrac Primer 2000 is a 100% solids, liquid applied primer with unique penetrating characteristics. It can be applied to asphalt, concrete and other sports and recreational surfaces. It has low viscosity, so it can be sprayed or rolled applied.

Features

- Cold Temperature Flexibility
- Excellent strength and elongation
- Good Freeze-Thaw Flexibility
- MDI Based-TDI free
- Outstanding working time
- Resilience

Color

Light Amber

Packaging

5-gallon pail (18.9 liters), net 45 lbs (20.4 kgs)

55-gallon drum (189 liters), net 450 lbs (204 kgs)

250-gallon tote (946 liters), net fill 2250 lbs (1022 kgs)

Installation

The surface to be coated should be dry and free of oil and debris. It can be applied with roller, or spray. Cure time is dependent on humidity and temperature. High temperature and/or high humidity will cure faster than low temperature and/or low humidity.

Technical Data

Appearance	Light Amber
NCO Content	9.4 ± 0.2%
Tensile Strength, ASTM D412	2000 ± 200 psi (13.8 ± 1.4 MPa)
Elongation, ASTM D-412	350 ± 50 %
Tear Resistance, Die C, ASTM D624	250 ± 50 pli (43.8 ± 8.8 KN/m)
Viscosity	950 ± 100 cps
VOC Content	0 g/l
Total Solids by Weight ASTM D2369	100%

Storage

Polytrac Primer 2000 has a shelf life of twelve (12) months from date of manufacture, in factory-sealed containers. Once a container has been opened, care should be taken to exclude moisture. Best temperature for storage is 75-95°F (25-35°C). If stored at higher temperatures, or if moisture is not excluded, shelf-life is reduced.

Safety

Wear protective equipment. Avoid contact with eyes and skin. Safety Data Sheets (SDS) are available from Polycoat Products. SDS are furnished to customers to provide handling and disposal information.

Warning

This product contains isocyanates.

Limited Warranty: Please read all information in the General Guidelines, Technical Data Sheets, Guide Specifications and Safety Data Sheets (SDS) before applying material. These products are for professional use only and to be applied by professionals who have prior experience and training with the use and application of our materials, and who are fully aware of all Federal, State and local rules, regulations, and code requirements for storage, transportation, handling, installation, and application. Published technical data and instructions are subject to change without notice. Contact your local representative or visit our website for current technical data, SDS, instructions, and project specific recommendations. We warrant our products to be free of manufacturing defects and that they will meet our current published physical properties within the shelf life of products.

Our sole responsibility shall be to replace that portion of the product which proves to be defective. There are no other warranties of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. We will not be liable for damages of any sort, including remote or consequential or punitive damages resulting from any claimed breach of any warranty whether expressed or implied. We will also not be responsible for use of this product in a manner to infringe on any patent held by others. No warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, adhesion, peeling, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and/or physical movement of the substrate or structural defects are also excluded from the limited warranty. We reserve the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Your sole and exclusive remedy against us shall be limited to the paid cost of the materials sufficient to replace any affected areas where product failure has occurred. The cost of replacement materials shall, in no event, exceed the value of the original purchase price of the products, subject to equitable reductions for time of use.

Disclaimer: We are not a professional contractor, engineering company, consultant, or applicator. We are a manufacturer and we are not a designer/engineer/applicator of record and we do not provide advice. We do not specifically review, endorse, or approve of any proposals, owner's specifications, project specifications, or other arrangements. All guidelines, recommendations, statements, and technical data contained herein are based on information and tests conducted in controlled conditions and do not represent applicable for all environments and we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. As a user, you will remain responsibility to satisfy yourself, based on your own information and test, to determine suitability of the product for your own intended use, application and job situation and you assume all risk and liability resulting from use of the products. We do not suggest or guarantee that any hazard listed herein are the only ones which may exist. We are not liable to any user or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. No recommendations or statements, whether verbal or in writing, shall be binding upon us except as provided herein, or as provided in writing and signed by an authorized corporate officer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Not responsible for typographical errors.

© 2026 Polycoat Products. All rights reserved. Revision 20260528.AG